



PW JIT SENG PLASTIC MATERIAL SDN BHD
PT 406, LORONG PERUSAHAAN BUKIT MINYAK 11,
TAMAN PERINDUSTRIAN BUKIT MINYAK, MK13,
14100, S.P.T, PENANG, MALAYSIA.
PHONE: 604-5070875 FAX: 604-5079864
EMAIL: info@pwjitseng.com.my

TECHNICAL DATA SHEET

RECYCLED POM BLACK

PROPERTIES	ASTM METHOD	UNITs	TYPICAL VALUES
<u>MECHANICAL</u>			
Tensile strength @ Yield	D-638	MPa	31.16
Tensile strength @ Break	D-638	MPa	57.41
Elongation @ Break	D-638	%	117.11
Flexural Strength	D-790	MPa	57.91
Flexural Modulus	D-790	MPa	61.63
Izod Impact Strength	D-256	KJ/m ²	8.02
<u>PHYSICAL</u>			
Specific Gravity	D-792	g/m ³	1.405
Melt Flow Index	D-1238	g/10min	6.72

The values presented in this data sheet are typical properties only. These properties are provided as a guide and may be changed without notice. It is not intended for specification purposes and not provided with any warranty. Users are strongly advised to confirm results by their own tests.

REV DATE: 07 MAY 2021