



PW JIT SENG PLASTIC MATERIAL SDN BHD
PT 406, LORONG PERUSAHAAN BUKIT MINYAK 11,
TAMAN PERINDUSTRIAN BUKIT MINYAK, MK13,
14100, S.P.T, PENANG, MALAYSIA.
PHONE: 604-5070875 FAX: 604-5079864
EMAIL: info@pwjitseng.com.my

TECHNICAL DATA SHEET

RECYCLED PP BLACK

PROPERTIES	ASTM METHOD	UNITs	TYPICAL VALUES
<u>MECHANICAL</u>			
Tensile strength @ Yield	D-638	MPa	11.76
Tensile strength @ Break	D-638	MPa	21.70
Elongation @ Break	D-638	%	82.14
Flexural Strength	D-790	MPa	23.62
Flexural Modulus	D-790	MPa	693.11
Izod Impact Strength	D-256	KJ/m ²	4.80
<u>PHYSICAL</u>			
Specific Gravity	D-792	g/m ³	1.00
Melt Flow Index	D-1238	g/10min	36.00

The values presented in this data sheet are typical properties only. These properties are provided as a guide and may be changed without notice. It is not intended for specification purposes and not provided with any warranty. Users are strongly advised to confirm results by their own tests.

REV DATE: 11 AUG 2022